



**MM**   **INCHES**

		S	M	L	XL
<b>A</b>	<b>head tube angle</b>	69.0 °	69.0 °	69.0 °	69.0 °
<b>B</b>	<b>head tube length</b>	100.0 mm	110.0 mm	125.0 mm	140.0 mm
<b>C</b>	<b>top tube horizontal</b>	575.0 mm	585.0 mm	610.0 mm	635.0 mm
<b>D</b>	<b>standover height</b>				
<b>E</b>	<b>BB offset</b>	-44.0 mm	-44.0 mm	-44.0 mm	-44.0 mm
<b>F</b>	<b>BB height</b>	295.0 mm	295.0 mm	295.0 mm	295.0 mm
<b>G</b>	<b>wheel base</b>	1,075.0 mm	1,085.0 mm	1,111.0 mm	1,137.0 mm
<b>H</b>	<b>BB center to toptube center</b>				
<b>I</b>	<b>BB center to top of seattube</b>	395.0 mm	440.0 mm	480.0 mm	530.0 mm
<b>J</b>	<b>seat angle</b>	73.0 °	73.0 °	73.0 °	73.0 °
<b>K</b>	<b>chainstay</b>	427.0 mm	427.0 mm	427.0 mm	427.0 mm
<b>L</b>	<b>reach</b>	398.0 mm	405.3 mm	426.0 mm	446.7 mm
<b>M</b>	<b>stack</b>	578.6 mm	587.9 mm	601.9 mm	615.9 mm
<b>N</b>	<b>stem length</b>	70.0 mm	80.0 mm	90.0 mm	100.0 mm