

XF 999 TR

MATTE BLACK/BLACK



SPECIFICATION

GEARS	1x12
FRAME	Carbon MTB Trail BF-1602, Trail Geometry, 130 mm travel, Boost 12x148 mm Thru axle, PressFit BB92, Alloy swingarm, Inner Cable Routing, Dropped post ready
HEAD SET	ACROS AZX-220 R4, Zero Stack 1-1/8"x1.5", BlockLock
FORK	RockShox Reba RL, Boost 15x110mm, OneLoc Sprint remote LO, 130 mm travel
REAR SHOCK	RockShox Monarch RT3, 184x44 mm, hardware: 25.4x8 mm/14.0x8 mm
SHIFTER	SRAM X01 Eagle Trigger Shifter 1x12
REAR DERAILLEUR	SRAM X01 Eagle
CRANKSET	SRAM X1-Carbon Eagle DUB Boost148 34T
BOTTOM BRACKET	SRAM DUB PF MTB92, shell 41x92 mm
FREEWHEEL/CASSETTE	SRAM XG-1275 Eagle 10-50T
CHAIN	SRAM GX Eagle
PEDALS	Not included
HANDLEBAR	Alloy flat 31.8 mm
STEM	ONE Race Superflat 31.8 mm
GRIPS	ESI Racers Edge silicone grips
BRAKES (FRONT/REAR)	SHIMANO DEORE XT BR-M8000, hydraulic disc, 180/160 mm rotor
SADDLE	Fi'zi:k Antares R7
SEAT POST	Crank Brothers Highline Dropper, 150 mm travel, 31.6x400 mm
FRONT HUB	DT Swiss X 1900 Spline 25 15x110 mm
REAR HUB	DT Swiss X 1900 Spline 25 12x148 mm
RIMS	DT Swiss X 1900 Spline 25
SPOKES	DT Swiss X 1900 Spline 25
TIRES	Schwalbe Nobby Nic SnakeSkin TL Easy ADDIX Speedgrip 29x2.35"
WEIGHT	11.8 kg

GEOMETRY

FRAME SIZE	15.5"(S)	17.5"(M)	19"(L)	21"(XL)
WHEEL SIZE	29"	29"	29"	29"
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE	72.7°	72.7°	72.7°	72.7°
EFFECTIVE TOP TUBE LENGTH (MM)	584	602	626	640
REACH (MM)	401	414	434	443
	606	618	627	639
HEAD TUBE LENGTH (MM)	100	110	120	130
HEAD TUBE ANGLE	68.8°	69.3°	69.3°	69.9°

FRAME SIZE	15.5"(S)	17.5"(M)	19"(L)	21"(XL)
CHAINSTAY LENGTH (MM)	430	430	430	430
BB DROP (MM)	28	28	28	28
WHEELBASE (MM)	1111	1122	1145	1152
SEAT POST DIAMETER (MM)	31.6	31.6	31.6	31.6
	400	400	400	400
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	80	90
CRANK LENGTH (MM)	170	175	175	175

MTB RACE XF CARBON

MTB RACE XF